




## DT-128

Pinless Moisture Meters Quickly indicate the moisture content of materials  
Depth of penetration about 20-40mm.  
Low battery indication MAX/MIN  
Function HOLD Function Auto Power Off  
White Backlit LCD Display.




<b>Features</b>	
Quickly indicate the moisture content of materials	
Depth of penetration about 20-40mm.	
Low battery indication	
MAX/MIN Function	
HOLD Function	
Auto Power Off	
White Backlit LCD Display	

<b>Specifications</b>	
Sensor Type	metal spheroid
Measuring Range	0 to 100 digit
Max Resolution	1
Battery	9V battery
Dimensions	189 x 47 x 35mm
Weight	178g



**Pinless Moisture Meters**

Quickly indicate the moisture content of materials  
Depth of penetration about 20-40mm.  
Low battery indication  
MAX/MIN Function  
HOLD Function  
Auto Power Off  
White Backlit LCD Display



**Table of Comparison**

Air Relative Humidity (%)	Air Relative Humidity		Structural Moisture	
0	10	20	30	40
50	60	70	80	90
100				
<div style="display: flex; justify-content: space-between; width: 100%;"> <span>Dry</span> <span>Normal</span> <span>Moist</span> </div>				

LCD Readout - COMPACT B

	0	10	20	30	40	50	60	70	80	90	100
Gypsum-sulphate based constr.mat./flooring - Wt./CM-%	0.3	0.5	1.4	2.0	2.5	2.7	%				
Cement based constr.mat. and flooring in CM-%	1.5	2.1	3.0	3.5	4.0	CM-%					
Cement based constr.mat. and flooring in weight-%	2.7	3.6	4.5	5.5	6.0	wt-%					

CM% = percentage value by carbide method

**Accessories:** 9V battery and gift box