




### Functions

- This unit was designed according to following standards:
  - International electrician committee standard: IEC PUB 651 TYPE2
  - US national standard: ANSI S1.4 TYPE2
- Accuracy up to +/-1.5dB
- Measurement range is 30 to 130dB
- Fast/Slow Time weighting selection
- Automatic backlight
- The maximum value holding function
- Auto power off 10 minutes
- A/C Frequency weighting selection
- Both AC and PWM signal output are available
- Calendar function
- 4700 data record function
- Connect with the PC through USB, provides data record downloading, real-time data sampling analysis, and printing graph&data functions.

### Specification

Measuring range	30dBA~130dBA
Accuracy	±1.5dB (reference sound pressure standard, 94dB@1KHz)
Frequency range	31.5Hz~8.5KHz
Frequency weighting	A & C
Digital Display	4digits
Analogy bar graph	1dB/1 bar graph
Resolution	0.1dB
Measuring level	30 to 80 , 50 to 100, 60 to 110, 80 to 130, 30 to 130
Dynamic range	50dB/100dB
Overload indication	OVER / UNDER
AC signal output	4Vrms/ full bar graph, output impedance is about 600 ohm
PWM signal output	Duty cycle = (0.01xdb value ÷ 3.3) x 100%
Dynamic characteristic	FAST (high speed)/SLOW (low speed)
PWM signal output	Duty cycle = (0.01xdb value ÷ 3.3) x 100%
Dynamic characteristic	FAST (high speed)/SLOW (low speed)
Calendar accuracy	±30seconds/day
Data storage quantity	4700
Power supply	6V (4PCS 1.5V Alkline battery)
Power supply	6V (4PCS 1.5V Alkline battery)
Power life	20h continuous use (Alkaline batteries)
Maximum value holding	MAX
Auto power off	10 minutes without operation
Microphone	1/2inch polarization capacitance microphone
Storage condition	-10~60°C, 10~70%RH
Weight	244g
Dimension	70*35*256mm



- Insert one end of USB wire into the USB socket on the unit, Plug another end of USB wire into the interface port on PC.