

## COM-80: EC/TDS HydroTester

NEW! The COM-80 is an economically priced, reliable EC/TDS meter that is ideal for testing applications such as hydroponics & gardening, pools & spas, aquariums & reef tanks, water ionizers, drinking water and more.

### FEATURES

- Measures electrical conductivity (EC), total dissolved solids (TDS). Excellent for nutrient testing.
- Four scales: EC:  $\mu\text{S}$ , mS; TDS: ppm, ppt
- Automatic Temperature Compensation (ATC)
- Water resistant
- Measurement Range: 0-9990  $\mu\text{S}$ ; 0-5000 ppm; 0-9.9 mS; 0-5.0 ppt
- Digital Calibration (push button) to any point within the meter's range
- Auto-off function, data-hold function and low-battery indicator
- Display: large and easy-to-read LCD screen includes simultaneous temperature reading.
- **Factory Calibrated:** The COM-80 meter is calibrated with a 1413  $\mu\text{S}$  solution. The meter can be recalibrated with digital calibration using the push buttons.
- Includes a protective cap and batteries.
- Need help deciding which meter is right for you? View our [TDS/EC Meter Selection Guide](#).

### SPECIFICATIONS

**EC Range:** 0 - 9990  $\mu\text{S}$ ; 0 - 9.9 mS

**TDS Range:** 0 - 5000 ppm (mg/L); 0 - 5.0 ppt

**Temperature Range:** 1-80 °C; 33-176 °F

**Resolution:** 1  $\mu\text{S}$ /ppm; 0.1 mS/ppt.

**Temp. resolution:** 0.1 °C/F

**Accuracy:** +/- 2%

**EC-to-TDS Conversion Factor:** NaCl (avg of 0.5).

**Calibration:** Digital calibration by push button.

**Probe:** Fixed

**Housing:** Water resistant

**Power source:** 3 x 1.5V button cell batteries (included) (model LR44 or equivalent)

**Dimensions:** 15.3 x 3.2 x 1.8 cm (6.0 x 1.3 x 0.7 inches)

**Weight:** 53.9g (1.9 oz)

**UPC:** 891144000229



YEAR WARRANTY

