

Model – GY-M15



Characteristics

1. High precision, high resolution.
2. The three measurement modes can switch freely (real-time, peak, first peak value).
3. Standard fruit hardness units in Kgf/cm² are shown.
4. The upper and lower limits can be set for statistical analysis, and the buzzer can be set beyond the limit for the alarm.
5. Automatic shutdown function: can set automatic shutdown time, automatic shutdown without operation to achieve power saving effect.
6. Power supply: 2pcs AAA battery (not included)
7. Automatic backlight and buzzer alarm function

Model number	GY-M15	GY-M30
Range	0.2~15 Kgf/cm ² (×10 ⁵ Pa)	0.4~30Kgf/cm ² (×10 ⁵ Pa)
Pressure head diameter	Φ11.1mm	Φ7.9mm
Load division value	0.01Kgf/cm ²	
Accuracy	±2%(10% to 100% of the full range)	
Insertion depth of indenter	10mm	
Power supply	2 Dry Battery # 7 (1.5V)	
Working temperature	5□~35□	
Transportation temperature	-10□~60□	
Relative humidity	15%~80%RH	
Work environment	No focal source and corrosive media around	
Net weight	About 0.4Kg	
Contour	124×60×31(mm)	

About Package

Product *1 piece

Hexagon nut M6*1 piece

Internal hexagonal cylindrical screw M4*6*4pcs

Internal hexagonal cylindrical screw M4*8*4pcs

Instructions*1 piec