

Single Angle Gloss Meter (WG60C)



Portable High precision 60 degree gloss meter

Product Description

This **WG60C gloss meter** is produced according to the national verification regulation standard, adopt long life light source, good repeatability, small volume, high precision and good stability. It is mainly used on coatings, printing ink, paint, paint, wood, marble, granite, polishing brick, brick of pottery and porcelain, plastic, paper, metal and non-metallic materials, more stable performance, more durable, more comfortable;

Specifications:

Product Name	Gloss meter
Model	WG60C
Measurement Range	0-200Gu
Application	Apply on paint, ink, stoving varnish, coating, wood products; Marble, granite, vitrified polished tile, pottery brick and porcelain, plastic, printing, paper; other metallic material.
Instrument Dimensions	159x49x72mm
Projection Angle	60°
Measuring Spot	(ellipse: long axis*minor axis) 14mm*61mm
Measuring Mode	Automatic measurement / manual measurement/single Measurement / average measurement and cross measurement for a variety of combination measuring mode
Standard Sample Setting	Manually setting standard and tolerance to determine "pass" or "failure".
Data Storage	No Set standard sample in any stored data, user-define the tolerance range

Language	English
Output	Connect the micro printer to realize real-time output of measured data
Division Value	0.1Gu
Repeatability	0.2Gu
Reproducibility	0.4Gu
Indication Error	1.0Gu
International Standard 60°	ISO—2813、ASTM—C584、ASTM—D523、DIN—67530、ASTM—D2457、JND-A60、JND-P60
National Standard 60°	GB 9754、GB 9966、GB 8807
Standard Accessories	Power adapter/user manual/warranty certification/standard board
Optional Accessories	micro-printer

SG OVERSEAS

Regd. Off.: C-101, DDA Flats, A-Block, Behind Siddhu Petrol Pump, Jahangir Puri, Delhi - 110033
 Blding 3664-65, Office: 102, First Floor, Shree Nath Market, Gali Shahtara, Delhi -110006
 Phone: 011-64621123, Web: www.sgoverseas.org, E-mail: sgoverseas@hotmail.com